

**contech**Tel. +972 4 6102000
www.contech.co.il

Server Cabinets

24U, 40U, 44U

WIDTH: 19" and 25"

HEIGHT: 24U - 44U

DEPTH: 900mm, 1000mm, 1100mm

TECHNICAL SPECIFICATIONS

ITEM	DESCRIPTION	RAW MATERIAL
ALUMINIUM FRAME	•BUILT OF 4 ALUMINIUM PROFILES	ALUMINIUM 6063
BOTTOM BASE	INCLUDING: •OPENINGS FOR CABLES ACCESS HOLES FOR FEET ASSEMBLY "OMEGA" PROFILE FOR GROUNDING KIT MOUNTING	STEEL 2mm
TOP PLATE	INCLUDING: •OPENINGS FOR CABLE ENTRY FROM 3 DIRECTIONS •4 OPENINGS FOR FANS	STEEL 2mm
TOP PLATE COVER	•FOR COVERING THE FANS	STEEL 1.25mm
FRONT DOOR	•HARDENED BRONZE GLASS DOOR OR BLANK STEEL DOOR OR VENTED STEEL DOOR WITH LOCK	6mm HARDENED SMOKED GLASS or STEEL 1.25mm
REAR DOOR	•BLANK STEEL OR VENTED STEEL , WITH LOCK	STEEL 1.25mm
SIDE PANELS	•2 REMOVABLE SIDE PANELS WITH ABS GADGETS ALLOWING EASY ACCESS TO THE CABINET FROM BOTH SIDES	STEEL 1.25mm
MOUNTING ANGLES	•4 ADJUSTABLE RACK MOUNTING ALUMINIUM OR ZINC COATED STEEL ANGLES FOR PROPER FIXING OF THE EQUIPMENT	ALUMINIUM 6063 or STEEL 2mm
INTERNAL DOORS FOR CABINETS 25"	•FOR COVERING THE CABLES IN RIGHT AND LEFT SIDES	STEEL 1.25mm
FEET / CASTERS	•STABILIZER FEET OR HEAVY DUTY CASTERS	
SHELVES	•PERFORATED OR BLANK SHELVES, FIXED OR SLIDING	STEEL 1.25mm
DRAWERS	•3U HEIGHT	STEEL 1.25mm
PAINTING	•TEXTURED EPOXY POWDER PAINT 60 -90 MICRONS STANDARD COLOURS RAL 7032 / 7035 OR AS PER CLIENT'S REQUEST	