

TECHNICAL SPECIFICATIONS

WIDTH: 19"

HEIGHT: 6U -25U

DEPTH: 300mm, 400mm, 500mm

Wall Mounted Cabinets**6U - 25U**

ITEM	DESCRIPTION	RAW MATERIAL
<i>BOTTOM COVER</i>	<i>INCLUDING:</i> • VENTILATION OPENINGS HOLES FOR FEET ASSEMBLY	C.R.S. 1.25mm
<i>TOP COVER</i>	<i>INCLUDING:</i> • OPENING FOR CABLE ENTRY • VENTILATION OPENINGS	C.R.S. 1.25mm
<i>SHELVES</i>	• PERFORATED OR BLANK SHELVES, AS PER CUSTOMER'S REQUEST	C.R.S. 1.25mm
<i>FRONT STRUCTURE</i>	2 STEEL PROFILES	C.R.S. 1.25mm
<i>FRONT DOOR</i>	• HARDENED SMOKED GLASS DOOR WITH LOCK OR STEEL DOOR WITH LOCK, AS PER CUSTOMER'S REQUEST	6mm HARDENED SMOKED GLASS or C.R.S. 1.25mm
<i>REAR PANEL</i>	• STEEL PANELS, WITH HOLES FOR WALL MOUNTING	C.R.S. 1.25/1.5mm
<i>SIDE PANELS</i>	• 2 REMOVABLE SIDE PANELS WITH ABS GADGETS FOR EASY ACCESS TO THE CABINET FROM BOTH SIDES	C.R.S. 2mm
<i>MOUNTING ANGLES</i>	• 4 ADJUSTABLE RACK MOUNTING GALVANIZED STEEL ANGLES PROVIDED WITH SQUARE HOLES FOR PROPER FIXING OF THE EQUIPMENT	C.R.S. 1.25mm
<i>STABILIZER FEET (Optional)</i>	• OPTION FOR WALL MOUNTED OR FLOOR STANDING, BY MOUNTING STABILIZER FEET	
<i>FRAME</i>	• BOTTOM, TOP, REAR PANEL AND FRONT STRUCTURE ARE ALL WELDED	
<i>FINISHING</i>	• TEXTURED EPOXY ELECTROSTATIC POWDER PAINT 60 - 90 MICRONS, STANDARD COLOURS RAL 7032 / 7035 OR AS PER CUSTOMER'S REQUEST	