

TECHNICAL SPECIFICATIONS

AVC Server Cabinets

40U, 42U, 44U

WIDTH: 600mm, 800mm HEIGHT: 40U, 42U, 44U DEPTH: 1000mm, 1100mm, 1200mm

ITEM	DESCRIPTION	RAW MATERIAL
FRAME	STRONG WELDED FRAME TO AVOID TWISTING	C.R. 2mm
BOTTOM BASE	INCLUDING: OPENINGS FOR CABLES ACCESS HOLES FOR FEET ASSEMBLY "OMEGA" PROFILE FOR GROUNDING KIT	C.R. 2mm
MOUNTING ANGLES	ZINC COATED STEEL ANGLES FOR PROPER FIXING OF THE EQUIPMENT	C.R. 2mm
FRONT DOOR	BLANK OR VENTED STEEL DOOR, WITH LOCK AND HIGH QUALITY HANDLE	C.R. 1.25mm
REAR DOOR	BLANK OR VENTED STEEL DOOR, WITH LOCK AND HIGH QUALITY HANDLE	C.R. 1.25mm
REMOVABLE SIDE PANELS	4 REMOVABLE SIDE PANELS WITH ABS GADGETS ALLOWING EASY ACCESS FROM BOTH SIDES	C.R. 1.25mm
FEET / CASTERS	STABILIZER FEET OR HEAVY DUTY CASTERS	C.R. 1.25mm
TOP COVER	• INCLUDING: OPENINGS FOR CABLE ENTRY FROM 3 DIRECTIONS • 4 OPENINGS FOR FANS	C.R. 1.25mm
SHELVES	PERFORATED OR BLANK, FIXED OR SLIDING SHELVES	C.R. 1.25mm
DRAWERS	• 3U HEIGHT	C.R. 1.25mm
COVER FOR FANS	FOR FANS' PROTECTION	C.R. 1.25mm
FINISHING	EPOXY POWDER PAINTING 60 -90 MICRONS RAL COLOUR PER ORDER	